



Charakteristiky

- Válcová stopka
- Pro řešení aplikací do kovu
- Ideální pro nelegované oceli
- Rychlá výměna díky dvojitému konci (HSS-D)
- dlouhá životnost

Katalogové číslo	Ø mm d	Celková délka mm L	Využitelná délka mm L ₁	Balení
2220253	2.5	57	30	10
2220303	3	61	33	10
2220323	3.2	65	36	10
2220353	3.5	70	39	10
2220404	4	75	43	10
2220424	4.2	75	43	10
2220454	4.5	80	47	10
2220505	5	86	52	10
2220525	5.2	86	52	10
2220555	5.5	93	57	10
2220605	6	93	57	10
2220656	6.5	101	63	10
2220706	7	109	69	10
2220756	7.5	109	69	10
2220807	8	117	75	10
2220857	8.5	117	75	10
2220908	9	125	81	10
2220958	9.5	125	81	10
2221008	10	134	87	10
2221109	11	142	94	5
2221210	12	151	101	5
2221310	13	151	101	5
2221410	14	160	109	5
2221511	15	169	114	5
2221612	16	178	120	5

HSS Spirálový vrták DIN 338, válcovaný za studena



Katalogové číslo	Ø mm d	Celková délka mm L	Využitelná délka mm L ₁	Balení
2230321	3.2	49	11	10
2230331	3.3	49	11	10
2230351	3.5	52	12	10
2230411	4.1	55	14	10
2230421	4.2	55	14	10
2230501	5	62	17	10
2230521	5.2	62	17	10

HSS-D Vrták dvoustranný, broušený



Katalogové číslo	Ø mm d	Počet kusů v setu	Balení
2220001	1-10 x 0.5	19	1
2220002	1-13 x 0.5	25	1

HSS-BX Vrták DIN 338, v kovovém pouzdru

